

## Teknor Apex Flexalloy® 9300-85 Polyvinyl Chloride Elastomer

Category : Polymer , Thermoplastic , Elastomer, TPE , Vinyl (PVC)

### Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTM Features: Good Flexibility, Oil Resistant, Ultra High MW, Recyclable, Good Thermal Stability, Good Weather ResistanceUses- Automotive Applications, TubingForms-PelletsProcessing-Extrusion, Injection MoldingInformation provided by Teknor Apex Company

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Teknor-Apex-Flexalloy-9300-85-Polyvinyl-Chloride-Elastomer.php](http://www.lookpolymers.com/polymer_Teknor-Apex-Flexalloy-9300-85-Polyvinyl-Chloride-Elastomer.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.28 g/cc	1.28 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85	85	15 seconds; ASTM D2240
Tensile Strength, Yield	19.7 MPa	2850 psi	ASTM D412
Elongation at Break	370 %	370 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-25.0 °C	-13.0 °F	ASTM D746

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China