

Teknor Apex Sinvicomp SFW 5500 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Availability: Asia Pacific Uses: Footwear; General Purpose Forms: Pellets Processing Method: Injection Molding Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-Sinvicomp-SFW-5500-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	ASTM D2240
Tensile Strength, Yield	16.2 MPa	2350 psi	9.8 in/min; ASTM D638
Elongation at Break	300 %	300 %	9.8 in/min; ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	190 Â°C @Time >=3600 sec	374 Â°F @Time >=1.00 hour	Congo Red; BS 2782

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China