

Tisan TISMOSET®

Category : Polymer , Thermoset

Material Notes:

Properties:Flame retardantHigh gloss surfaceImproved thermal and electrical strengthHigh impact strengthMinimized shrinkage at the presence of moldingHigh melting flow indexReduced moisture absorptionEasy processingReasonable pricesApplication: Can be substituted with thermoplastics in numerous applications including the electric industry, house appliances, bath, and kitchen applications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Tisan-TISMOSET.php

Physical Properties	Metric	English	Comments
Density	1.475 - 1.49 g/cc	0.05329 - 0.0538 lb/in ³	ISO 1183
Apparent Bulk Density	0.600 - 0.620 g/cc	0.0217 - 0.0224 lb/in ³	ISO 60

Mechanical Properties	Metric	English	Comments
Izod Impact, Notched (ISO)	2.75 - 2.95 kJ/m ²	1.31 - 1.40 ft-lb/in ²	ISO 180
Izod Impact, Unnotched (ISO)	5.50 - 5.55 kJ/m ²	2.62 - 2.64 ft-lb/in ²	ISO 180

Thermal Properties	Metric	English	Comments
Heat Distortion Temperature	130 °C	266 °F	ISO 75-2
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China