

## Total HDPE HD 6081 High Density Polyethylene - Injection Molding

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

### Material Notes:

HD 6081 is a high density polyethylene with very good organoleptic properties, rigidity and processability. It is especially suited for the production of caps & closures for non-carbonated drinks by injection molding. Other typical applications include other caps & closures, pails & crates and general-purpose injection-molded articles. This grade does not contain a slip agent. Information provided by Total Petrochemicals.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Total-HDPE-HD-6081-High-Density-Polyethylene-Injection-Molding.php](http://www.lookpolymers.com/polymer_Total-HDPE-HD-6081-High-Density-Polyethylene-Injection-Molding.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.960 g/cc	0.960 g/cc	ISO 1183
Melt Flow	8.0 g/10 min @Load 2.16 kg, Temperature 190 °C	8.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133/D

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	29.0 MPa	4210 psi	ISO 527
Tensile Modulus	1.30 GPa	189 ksi	ISO 527

Thermal Properties	Metric	English	Comments
Melting Point	133 °C	271 °F	ISO 11357

Processing Properties	Metric	English	Comments
Processing Temperature	<= 250 °C	<= 482 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China