

Total LDPE LA 0710 Low Density Polyethylene - Extrusion Coating

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE , Low Density Polyethylene (LDPE), Extrusion Grade

Material Notes:

LDPE LA 0710 is a low density polyethylene made by a high pressure autoclave process without antioxidant. Application examples: coating of paper, paperboard, aluminum. High draw down, low neck in. Information provided by Total Petrochemicals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Total-LDPE-LA-0710-Low-Density-Polyethylene-Extrusion-Coating.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.918 g/cc	0.918 g/cc	ISO 1183
Melt Flow	7.5 g/10 min @Load 2.16 kg, Temperature 190 °C	7.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	12.0 MPa	1740 psi	ISO 527-2
Tensile Strength, Yield	9.00 MPa	1310 psi	ISO 527-2
Elongation at Break	450 %	450 %	ISO 527-2
Modulus of Elasticity	0.170 GPa	24.7 ksi	ISO 527-2

Thermal Properties	Metric	English	Comments
Melting Point	108 °C	226 °F	ISO 11357
Vicat Softening Point	90.0 °C	194 °F	ISO 306

Processing Properties	Metric	English	Comments
Processing Temperature	200 - 320 °C	392 - 608 °F	
Melt Temperature	260 - 320 °C	500 - 608 °F	Die Melt Temp

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China

