

Total PPC 5945WZ Polypropylene, Impact Copolymer

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Molded

Material Notes:

TOTAL Petrochemicals Polypropylene 5945WZ is a nucleated impact copolymer with a Melt Flow index of 80 g/10 min. TOTAL Polypropylene 5945WZ is characterized by very low warpage, improved stiffness, and high impact resistance balance, excellent antistatic properties and has been formulated to allow faster cycling through early demolding. Total Polypropylene 5945WZ complies with all applicable FDA regulations for food contact applications. Total Polypropylene 5945WZ has been developed specifically for the injection molding of thin-walled articles and compounding. Information provided by Total Petrochemicals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Total-PPC-5945WZ-Polypropylene-Impact-Copolymer.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.905 g/cc	0.905 g/cc	ASTM D1505
Melt Flow	80 g/10 min	80 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	25.0 MPa	3630 psi	ASTM D638
Elongation at Yield	6.0 %	6.0 %	ASTM D638
Flexural Modulus	1.25 GPa	181 ksi	ASTM D790
Izod Impact, Notched	0.850 J/cm	1.59 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	160 - 165 °C	320 - 329 °F	TOTAL Method
Deflection Temperature at 0.46 MPa (66 psi)	110 °C	230 °F	Pressure unspecified, Unannealed; ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China