

Tra-Con Tra-Bond 724-20 Polyurethane Adhesive

Category: Polymer, Adhesive, Thermoset, Polyurethane, TS

Material Notes:

TRA-BOND 724-20 polyurethane adhesive is designed for good adhesion, providing strong, resilient bonds to a wide variety of substrates including aluminum, solder, nylon, mylar and steel. TRA-BOND 724-20 offers several curing options, including curing at room temperature. This adhesive is a variation of TRA-BOND 724-14C adhesive, which has been modified to provide improved bondline control.Information provided by Tra-Con Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Tra-Con-Tra-Bond-724-20-Polyurethane-Adhesive.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	
Adhesive Bond Strength	12.4 MPa	1800 psi	Lap shear, alum to alum

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	
	@Temperature 95.0 °C	@Temperature 203 °F	
	180 min	3.00 hour	
	@Temperature 75.0 °C	@Temperature 167 °F	
	4320 min	72.0 hour	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Shelf Life	3.00 Month	3.00 Month	Estimated
	@Temperature -40.0 °C	@Temperature -40.0 °F	

Descriptive Properties	Value	Comments
Color	Amber	
Working Life minutes	30	Estimated

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China

