

## UBE 7128B Nylon 6/12 Copolymer

Category : Polymer , Thermoplastic , Nylon , Nylon 612 , Nylon 612, Impact Modified

**Material Notes:**

Description: UBESTA Nylon 12 Copolymer Information provided by UBE.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_UBE-7128B-Nylon-612-Copolymer.php](http://www.lookpolymers.com/polymer_UBE-7128B-Nylon-612-Copolymer.php)

Physical Properties	Metric	English	Comments
Density	1.06 g/cc	0.0383 lb/in <sup>3</sup>	ASTM D792
Melt Flow	4.2 g/10 min @Load 1.00 kg, Temperature 190 °C	4.2 g/10 min @Load 2.20 lb, Temperature 374 °F	ASTM D1238R

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	>= 27.0 MPa	>= 3920 psi	ASTM D638
Tensile Strength, Yield	9.00 MPa	1310 psi	ASTM D638
Elongation at Break	>= 300 %	>= 300 %	ASTM D638
Flexural Strength	26.0 MPa	3770 psi	ASTM D790
Flexural Modulus	0.780 GPa	113 ksi	ASTM D790
Izod Impact, Notched	0.800 J/cm	1.50 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	135 °C	275 °F	ASTM D3418

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China