

UBE J5019 Polyethylene

Category: Polymer, Thermoplastic, Polyethylene (PE)

Material Notes:

Description: UBE Polyethylene is polymerized at high pressure using a tubular reactor. Production conditions are strictly controlled ensuring the product's superior physical and mechanical properties including transparency and glossiness, and making the material ideal for further processing. Transparency: Superior transparency and glossiness even for applications involving processing of thick objects. Ease of Processing: Excellent fluidity and melt tension characteristics suited to a wide range of molding methods. Inflation molding - can be molded into even thick or wide products with superior bubble stability. Extrusion lamination - can be drawn down even at high speed. Blow molding - can be molded producing a very smooth surface. Injection molding - can be molded even into very thin products. Strength: Good balance in length and breadth with superior tearing strength lengthways. Application: Injection molding Features: Fluidity Information provided by UBE.

Order this product through the following link: http://www.lookpolymers.com/polymer_UBE-J5019-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.919 g/cc	0.0332 lb/in³	ASTM D1505
Melt Flow	50 g/10 min	50 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	45	45	ASTM D2240
Tensile Strength at Break	8.00 MPa	1160 psi	ASTM D638
Elongation at Break	250 %	250 %	ASTM D638
Flexural Strength	11.0 MPa	1600 psi	Olsen; ASTM D747

Thermal Properties	Metric	English	Comments
Vicat Softening Point	78.0 °C	172 °F	ASTM D1525
Brittleness Temperature	-30.0 °C	-22.0 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China