

UBE UMERIT 2500F Metallocene LLDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , LLDPE , Linear Low Density Polyethylene (LLDPE), Injection Molded

Material Notes:

Description: UBE Super Polyethylene Umerit® is an ethylene-olefin copolymer made by UBE using the metallocene catalytic method. The metallocene catalytic method results in superior physical properties by being able to acquire any targeted molecular structures. Specific

Notes for this Grade: UMERIT® 2500F offer various excellent properties: Reduced motor load at processing, Draw resonance at high-speed drawing hardly occurs. Information provided by UBE.

Order this product through the following link:

http://www.lookpolymers.com/polymer_UBE-UMERIT-2500F-Metallocene-LLDPE.php

Physical Properties	Metric	English	Comments
Density	0.923 g/cc	0.0333 lb/in ³	ASTM D1505
Environmental Stress Crack Resistance	1000 hour	1000 hour	F50; ASTM D1693
Melt Flow	4.0 g/10 min	4.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	56	56	ASTM D2240
Tensile Strength, Yield	36.0 MPa	5220 psi	ASTM D638
Elongation at Break	760 %	760 %	ASTM D638
Tensile Modulus	0.340 GPa	49.3 ksi	Bending Modulus; ASTM D790

Thermal Properties	Metric	English	Comments
Melting Point	119 °C	246 °F	UBE method
Vicat Softening Point	107 °C	225 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China