

UBE V206 Polyethylene

Category: Polymer, Thermoplastic, Polyethylene (PE)

Material Notes:

Description: UBE Polyethylene is polymerized at high pressure using a tubular reactor. Production conditions are strictly controlled ensuring the product's superior physical and mechanical properties including transparency and glossiness, and making the material ideal for further processing. Transparency: Superior transparency and glossiness even for applications involving processing of thick objects. Ease of Processing: Excellent fluidity and melt tension characteristics suited to a wide range of molding methods. Inflation molding - can be molded into even thick or wide products with superior bubble stability. Extrusion lamination - can be drawn down even at high speed. Blow molding - can be molded producing a very smooth surface. Injection molding - can be molded even into very thin products. Strength: Good balance in length and breadth with superior tearing strength lengthways. Application: Film Features: High transparency Glossiness Information provided by UBE.

Order this product through the following link: http://www.lookpolymers.com/polymer_UBE-V206-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc	0.0332 lb/in ³	ASTM D1505
Vinyl Acetate Content	6.0 %	6.0 %	Ube method
Melt Flow	2.0 g/10 min	2.0 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	96	96	ASTM D2240
Tensile Strength at Break	19.0 MPa	2760 psi	ASTM D638
Elongation at Break	730 %	730 %	ASTM D638
Flexural Strength	10.0 MPa	1450 psi	Olsen; ASTM D747

Thermal Properties	Metric	English	Comments	
Vicat Softening Point	86.0 °C	187 °F	ASTM D1525	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China