

UCAR Carbon UCAR® CGW Isostatic Molded Graphite

Category: Carbon, Graphite

Material Notes:

Isostatically molded grade CGW is an ATJ-based material that has been processed to higher density and strength. Grade CGW is characterized by low permeability, erosion resistance and surface hardness. Typical Applications: Continuous casting dies Hot pressing dies and molds Tabular property data is typical. Information provided by UCAR Carbon Company, a GrafTech International Ltd. company.

Order this product through the following link:

http://www.lookpolymers.com/polymer_UCAR-Carbon-UCAR-CGW-Isostatic-Molded-Graphite.php

Physical Properties	Metric	English	Comments
Density	1.82 g/cc	0.0658 lb/in³	
Particle Size	25 μm	25 μm	
Ash	0.090 %	0.090 %	

Mechanical Properties	Metric	English	Comments
Flexural Strength	36.5 MPa	5300 psi	

Thermal Properties	Metric	English	Comments
CTE, linear	2.90 μm/m-°C	1.61 μin/in-°F	
	@Temperature 20.0 - 100 °C	@Temperature 68.0 - 212 °F	
Thermal Conductivity	120 W/m-K	833 BTU-in/hr-ft ² -°F	

Electrical Properties	Metric	English	Comments
Electrical Resistivity	0.00117 ohm-cm	0.00117 ohm-cm	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China