

Unifrax Fiberwall® Bonded 26 Bonded Module System

Category : Ceramic

Material Notes:

Fiberfrax Bonded modules and Hefty-Loc alloy steel hardware are the components of the Hefty-Loc module lining system. The Hefty-Loc system provides an insulation lining for a variety of heat processing equipment. Bonded modules used in the Hefty-Loc system offer the same advantages as Fiberwall Anchor-Loc® module linings and layered Fiberwall construction when compared to refractory construction. These advantages are: Faster temperature cycling Lower heat storage Lower fuel costs Increased productivity Resistance to thermal shock and spalling Lower installation cost Easier repairs Reduced maintenance The Hefty-Loc system is used for a wide range of thermal requirements in applications up to 2100°F. Typical applications for the Hefty-Loc system are as follows: Stress relieving furnaces Annealing furnaces Car bottom heat treating furnaces Process heaters Furnace, kiln and boiler linings Incineration equipment and stack linings Field steam generators Aluminum soaking pits and homogenizing furnaces Information Provided by Unifrax I LLC

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unifrax-Fiberwall-Bonded-26-Bonded-Module-System.php

Physical Properties	Metric	English	Comments
Density	0.149 g/cc	0.00538 lb/in ³	
	0.171 g/cc	0.00619 lb/in ³	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1343 °C	2449 °F	Recommended Operating Temperature

Descriptive Properties	Value	Comments
Construction	Folded Durablanket 2600	
Temperature Grade (°C)	1427	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China