

Unipetrol 70/100 Road Bitumen

Category : Fluid

Material Notes:

At normal temperatures, road bitumens are semi-solid to solid homogeneous bitumen substances. They are produced as residual fractions of vacuum distillation of the atmospheric crude oil residual fraction, by blowing crude oil residual fractions or by mixing oxidized asphalts with crude oil residual fractions. Road bitumens are used for the production of penetration macadam, packaging mixtures, cast asphalts, for the construction and maintenance of asphalt roads, sidewalks, for the bottom layer of roads and in the production of asphalt concrete. Information provided by Unipetrol RPA

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unipetrol-70100-Road-Bitumen.php

Mechanical Properties	Metric	English	Comments
Penetration	>= 46	>= 46	remnant

Thermal Properties	Metric	English	Comments
Ring & Ball Softening Point	>= 45.0 °C	>= 113 °F	after aging @ 163°C
	43.0 - 51.0 °C	109 - 124 °F	

Descriptive Properties	Value	Comments
Breaking Point °C	-10	
Increase in Softening Point (°C)	11	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China