

## Unipetrol Grade 2 Diesel Oil

Category : Fluid , Solvent

### Material Notes:

Diesel oils are a mix of liquid hydrocarbons obtained from crude oil through distillation and hydrogenation refining, usually boiling within to 370°C. They may contain additives to improve their application characteristics such as depressants, detergents, lubrication additives and corrosion inhibitors. Diesel oils are used as fuel for diesel engines or fuel for some types of gas turbines as well. Information provided by Unipetrol RPA

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Unipetrol-Grade-2-Diesel-Oil.php](http://www.lookpolymers.com/polymer_Unipetrol-Grade-2-Diesel-Oil.php)

Physical Properties	Metric	English	Comments
Density	0.800 - 0.840 g/cc	0.0289 - 0.0303 lb/in <sup>3</sup>	
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measure	1.5 - 4.0 cSt	1.5 - 4.0 cSt	
	@Temperature 40.0 °C	@Temperature 104 °F	
Ash	<= 0.010 %	<= 0.010 %	
Evaporation Loss	10 %	10 %	
	@Temperature 180 °C	@Temperature 356 °F	
	>= 95 %	>= 95 %	
	@Temperature 340 °C	@Temperature 644 °F	

Thermal Properties	Metric	English	Comments
Flash Point	>= 55.0 °C	>= 131 °F	nad

Component Elements Properties	Metric	English	Comments
Sulfur, S	0.035 %	0.035 %	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.020 %	<= 0.020 %	

Descriptive Properties	Value	Comments
Cetane index, min	46	
Cetane Number, min	48	
Filtrability °C, max	-32	

Descriptive Properties	Value	Comments
Total Impurity Content %, max	0.0024	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China