

Unipetrol Grade B Diesel Oil

Category : Fluid , Solvent

Material Notes:

Diesel oils are a mix of liquid hydrocarbons obtained from crude oil through distillation and hydrogenation refining, usually boiling within to 370°C. They may contain additives to improve their application characteristics such as depressants, detergents, lubrication additives and corrosion inhibitors. Diesel oils are used as fuel for diesel engines or fuel for some types of gas turbines as well. Information provided by Unipetrol RPA

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unipetrol-Grade-B-Diesel-Oil.php

Physical Properties	Metric	English	Comments
Density	0.820 - 0.845 g/cc	0.0296 - 0.0305 lb/in ³	
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measure	2.0 - 4.5 cSt	2.0 - 4.5 cSt	
Ash	<= 0.010 %	<= 0.010 %	
Evaporation Loss	<= 65 %	<= 65 %	
	@Temperature 250 °C	@Temperature 482 °F	
	>= 85 %	>= 85 %	
	@Temperature 350 °C	@Temperature 662 °F	
	>= 95 %	>= 95 %	
	@Temperature 360 °C	@Temperature 680 °F	

Thermal Properties	Metric	English	Comments
Flash Point	>= 55.0 °C	>= 131 °F	nad

Component Elements Properties	Metric	English	Comments
Sulfur, S	0.0050 %	0.0050 %	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.020 %	<= 0.020 %	

Descriptive Properties	Value	Comments
Cetane index, min	46	
Cetane Number, min	51	

Descriptive Properties	Value	Comments
Total Impurity Content %, max	0.0024	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China