

## Unipetrol Light Stabilized Oil Hydrogenate

Category : Fluid , Solvent

### Material Notes:

Stabilized oil hydrogenates are a fraction boiling above approximately 250°C, obtained from crude oil through distillation and mild hydrocracking. They are a mixture of light colour hydrocarbons of semi-solid to pasty character under normal conditions, without any notable water and mechanical impurity content. Stabilized oil hydrogenates are special intermediates which, after distillation treatment and dewaxing by customer, serve mainly as a basic component for primary lube oil production, or for production of special oils and liquids.

Types: Stabilized oil hydrogenates are produced in types agreed with the customer in compliance with respective sales agreement. Light, medium and heavy stabilized oil hydrogenates are produced with wide viscosity range and viscosity index 80 to 120. Information provided by Unipetrol RPA

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Unipetrol-Light-Stabilized-Oil-Hydrogenate.php](http://www.lookpolymers.com/polymer_Unipetrol-Light-Stabilized-Oil-Hydrogenate.php)

Physical Properties	Metric	English	Comments
Density	0.828 - 0.871 g/cc	0.0299 - 0.0315 lb/in <sup>3</sup>	
	@Temperature 15.0 °C	@Temperature 59.0 °F	
Viscosity Measurement	81.0 - 112	81.0 - 112	Viscosity Index after dewaxing
Evaporation Loss	3.0 %	3.0 %	
	@Temperature 275 - 305 °C	@Temperature 527 - 581 °F	
ASTM Color	<= 1.0	<= 1.0	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China