

Unipetrol Pyrolysis Fuel Oil

Category : Fluid , Solvent

Material Notes:

Pyrolysis fuel oil is a mixture of higher boiling aromatic hydrocarbons, produced as a by-product during pyrolysis of oil fractions. It is a dark, viscous liquid with pour point approx. 15 °C. Pyrolysis fuel oil is classified according to EC Directives as a hazardous substance with carcinogenic components. Pyrolysis fuel oil is used as a raw material for manufacture of carbon black, it can also be used as a low-sulphur fuel oil. Information provided by Unipetrol RPA

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unipetrol-Pyrolysis-Fuel-Oil.php

Physical Properties	Metric	English	Comments
Density	<= 1.15 g/cc @Temperature 15.0 °C	<= 0.0415 lb/in ³ @Temperature 59.0 °F	EN ISO 3675
Viscosity Measure	<= 70 cSt	<= 70 cSt	EN ISO 3104
Ash	<= 0.10 %	<= 0.10 %	

Thermal Properties	Metric	English	Comments
Distillation Temperature	>= 200 °C	>= 392 °F	EN ISO 3405
	>= 290 °C	>= 554 °F	EN ISO 3405
Flash Point	>= 101 °C	>= 214 °F	EN ISO 2592

Component Elements Properties	Metric	English	Comments
Free Water	<= 0.10 %	<= 0.10 %	
Sulfur, S	1.0 %	1.0 %	

Descriptive Properties	Value	Comments
Calorific Value (Mj/kg)	37 - 40	
Mechanical Impurities and Water %	0.1	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China