

## Unipetrol R2 Heavy Fuel Oil

Category : Fluid , Solvent

### Material Notes:

Heavy fuel oil R2 is a mixture of mostly higher hydrocarbons obtained from crude oil through distillation and other refining processes. It may contain additives to lower its freezing point, or additives to improve other characteristics. Heavy fuel oil R2 is used widely throughout industries. Application fields depend on technical as well as economic aspects, and specific operational circumstances of the consumer. Information provided by Unipetrol RPA

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Unipetrol-R2-Heavy-Fuel-Oil.php](http://www.lookpolymers.com/polymer_Unipetrol-R2-Heavy-Fuel-Oil.php)

Physical Properties	Metric	English	Comments
Density	0.990 g/cc	0.0358 lb/in <sup>3</sup>	
	@Temperature 20.0 °C	@Temperature 68.0 °F	
Viscosity Measure	<= 10 cSt	<= 10 cSt	
	@Temperature 150 °C	@Temperature 302 °F	
	<= 57 cSt	<= 57 cSt	
	@Temperature 100 °C	@Temperature 212 °F	
	<= 118 cSt	<= 118 cSt	
	@Temperature 80.0 °C	@Temperature 176 °F	
Ash	<= 0.14 %	<= 0.14 %	

Thermal Properties	Metric	English	Comments
Melting Point	40.0 °C	104 °F	
Flash Point	>= 110 °C	>= 230 °F	in open crucible

Component Elements Properties	Metric	English	Comments
Sulfur, S	<= 1.0 %	<= 1.0 %	Low sulfur
	<= 2.0 %	<= 2.0 %	Mid sulfur
	<= 3.0 %	<= 3.0 %	High sulfur

Descriptive Properties	Value	Comments
Mechanical Impurities and Water %	1	

Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China