

Valley Adhesives EM-240 Low Temperature Application Glue Stick

Category : Polymer , Adhesive , Thermoset

Material Notes:

Valley Adhesives EM-240 Low Temperature Application Glue Stick Bonds many woods and wood composites; Excellent for woodworking and cabinetry.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Valley-Adhesives-EM-240-Low-Temperature-Application-Glue-Stick.php

Physical Properties	Metric	English	Comments
Viscosity	7850 cP	7850 cP	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	78	78	
Tensile Strength, Ultimate	2.28 MPa	331 psi	
Elongation at Break	153 %	153 %	
Shear Strength	2.54 MPa	369 psi	
Peel Strength	2.96 kN/m	16.9 pli	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	60.0 °C	140 °F	Heat Resistance Value at 2 psi.
Softening Point	196 °C	385 °F	

Processing Properties	Metric	English	Comments
Cure Time	0.0833 min	0.00139 hour	Hot tack
Pot Life	0.50 min	0.50 min	Open Time

Descriptive Properties	Value	Comments
Color	Amber	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China