

Victrex® PEEK 600P Polyetheretherketone (discontinued **)

Category: Polymer, Thermoplastic, Polyketone, Polyetheretherketone (PEEK), Polyetheretherketone, PEEK, Unreinforced

Material Notes:

Product Description: High performance thermoplastic material, unreinforced PolyEtherEtherKetone (PEEK), semi crystalline, coarse powder for extrusion compounding, low flow, FDA food contact compliantInformation provided by Victrex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Victrex-PEEK-600P-Polyetheretherketone-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	1.30 g/cc	0.0470 lb/in³	ISO 1183
Viscosity	450000 cP	450000 cP	Melt; ISO 11443
	@Temperature 400 °C	@Temperature 752 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	90.0 MPa	13100 psi	Result based on similar products; ISO 527
Elongation at Break	30 %	30 %	Result based on similar products; ISO 527
Tensile Modulus	3.70 GPa	537 ksi	Result based on similar products; ISO 527
Flexural Strength	150 MPa	21800 psi	Result based on similar products; ISO 178
Flexural Modulus	4.10 GPa	595 ksi	Result based on similar products; ISO 178
Izod Impact, Notched (ISO)	7.50 kJ/m²	3.57 ft-lb/in ²	Result based on similar products; ISO 180/A
Izod Impact, Unnotched (ISO)	NB	NB	Result based on similar products; ISO 180/U

Thermal Properties	Metric	English	Comments
Melting Point	343 °C	649 °F	ISO 11357
Glass Transition Temp, Tg	143 °C	289 °F	Onset; ISO 11357

Descriptive Properties	Value	Comments
Color	Natural	

Contact Songhan Plastic Technology Co.,Ltd.



Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China