

Westlake EC808AA Low Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

WESTLAKE low-density polyethylene EC808 is a general-purpose formulation used for injection molding, general-purpose extrusion coating and laminating. It can be drawn down to low coating weights, is processable at high speeds, has a good moisture barrier, and is heat-sealable at low temperatures. Application/Uses Foil Food packaging Laminating Playing cards Toys/sporting goods FDA: This material complies with FDA regulations in 21 CFR, section 177.1520. Kosher Compliant. All information provided by Westlake Chemical

Order this product through the following link:

http://www.lookpolymers.com/polymer_Westlake-EC808AA-Low-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in ³	ASTM D1505
Melt Flow	7.0 g/10 min @Load 2.16 kg, Temperature 190 °C	7.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	10.0 MPa	1450 psi	500mm/min; ASTM D638 Type IV Specimen
Elongation at Break	400 %	400 %	500mm/min; ASTM D638 Type IV Specimen
2% Secant Modulus	0.207 GPa	30.0 ksi	12.7mm/min; ASTM D790

Processing Properties	Metric	English	Comments
Melt Temperature	149 - 166 °C	300 - 330 °F	

Descriptive Properties	Value	Comments
Process	Coating Injection Molding	
Region	US & Canada	Bamberger Polymers Distribution

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China