

## Westlake Tymax™ GA4402 Anhydride Modified Linear Low Density Polyethylene (Developmental Resin)

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

### Material Notes:

Westlake GA4402 is an anhydride modified linear low density polyethylene designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a co-extruded tie layer in multilayer film applications. Westlake GA4402 is designed to tie PE to resins that typically have poor bonding characteristics such as polyamide and EVOH. Its applications include: blown film, packaging, and tie layer.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Westlake-Tymax-GA4402-Anhydride-Modified-Linear-Low-Density-Polyethylene-Developmental-Resin.php](http://www.lookpolymers.com/polymer_Westlake-Tymax-GA4402-Anhydride-Modified-Linear-Low-Density-Polyethylene-Developmental-Resin.php)

Physical Properties	Metric	English	Comments
Density	0.923 g/cc	0.0333 lb/in <sup>3</sup>	ASTM D4883
Melt Flow	2.0 g/10 min @Load 2.16 kg, Temperature 190 °C	2.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	122 °C	252 °F	ASTM D3418
Vicat Softening Point	97.0 °C	207 °F	ASTM D3418

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China