

## Westlake Tymax™ GT1057 Anhydride Modified Acrylate Copolymer

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

### Material Notes:

Product Description: Westlake GT1057 is an anhydride modified low density polyethylene designed as an extrusion coating and laminating tie-layer. Westlake GT1057 provides excellent adhesion to polyolefins, polyamides, aluminum foil, and EVOH as a coextruded tie-layer or a laminating layer. Application/Uses: Blow Film Packaging Tie-layer

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Westlake-Tymax-GT1057-Anhydride-Modified-Acrylate-Copolymer.php](http://www.lookpolymers.com/polymer_Westlake-Tymax-GT1057-Anhydride-Modified-Acrylate-Copolymer.php)

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in <sup>3</sup>	ASTM D4883
Melt Flow	7.5 g/10 min @Load 2.16 kg, Temperature 190 °C	7.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	106 °C	223 °F	DSC; ASTM D3418
Vicat Softening Point	87.0 °C	189 °F	DSC; ASTM D3418

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China