

## Westlake Tymax™ GT4524 Anhydride Modified Linear Low Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

### Material Notes:

Westlake GT4524 is an anhydride modified linear low density polyethylene designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a coextruded tie layer in multilayer film applications. Westlake GT4524 is designed to tie LLDPE to resins that typically have poor bonding characteristics such as polyamide and EVOH. Its applications include: blown film, packaging, and tie-layer.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Westlake-Tymax-GT4524-Anhydride-Modified-Linear-Low-Density-Polyethylene.php](http://www.lookpolymers.com/polymer_Westlake-Tymax-GT4524-Anhydride-Modified-Linear-Low-Density-Polyethylene.php)

Physical Properties	Metric	English	Comments
Density	0.910 g/cc	0.0329 lb/in <sup>3</sup>	ASTM D4883
Melt Flow	0.65 g/10 min @Load 2.16 kg, Temperature 190 °C	0.65 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	120 °C	248 °F	DSC; ASTM D3418
Crystallization Temperature	88.0 °C	190 °F	DSC; ASTM D3418

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China