

## Westlake Tymax™ GT7058 Anhydride Modified Acrylate Copolymer

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

### Material Notes:

Westlake GT7058 is an anhydride modified acrylate copolymer designed for blown film extrusion that contains no slip and no antiblock additives. This resin is designed to function as a coextruded tie layer in multilayer film applications. Westlake GT7058 is designed to tie polyethylene to resins that typically have poor bonding characteristics such as polyamide and EVOH. Its applications include: blown film, packaging, and tie-layer.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Westlake-Tymax-GT7058-Anhydride-Modified-Acrylate-Copolymer.php](http://www.lookpolymers.com/polymer_Westlake-Tymax-GT7058-Anhydride-Modified-Acrylate-Copolymer.php)

Physical Properties	Metric	English	Comments
Density	0.943 g/cc	0.0341 lb/in <sup>3</sup>	ASTM D4883
Methyl Acrylate Content	24 %	24 %	Westlake
Melt Flow	2.7 g/10 min @Load 2.16 kg, Temperature 190 °C	2.7 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	74.0 °C	165 °F	DSC; ASTM D3418
Crystallization Temperature	43.0 °C	109 °F	DSC; ASTM D3418

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China